

Dokivision

DESKTOP SCANNER DTS301



High-Speed Motion Tolerance

With an impressive 3.2m/s motion tolerance, it captures fast-moving barcodes effortlessly, significantly speeding up checkout processes.



Precision Imaging

Equipped with a 640*800 CMOS sensor and White LED illumination, it ensures accurate reading of both paper labels and digital screens.



Durable 360° Scanning

It features 360° omnidirectional scanning capabilities and is built with an IP54 protection rating, making it highly adaptable and robust for busy desktop environments.



Supermarket



Payment



Self-order



Mall



Checkout



Parking

Category / Item	Specification Details
PERFORMANCE	
Image Sensor	CMOS
Resolution	640*800
Illumination Aiming	White LED Red LED
2D Symbolologies	PDF417, MicroPDF417, MicroQR, Data Matrix, QR, Aztec
1D Symbolologies	EAN-8, EAN-13, EAN-13 2 add-on, EAN-13 5 add-on, ISSN, ISBN, UPC-A, UPC-E, Code11, Code 32, Code 39, Code 39 FULLASCII, Code 93, Code 128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, GS1-128, GS1 DataBar (RSS14) GS1 DataBar LimitedGS1 DataBar Expanded
Typical Decode Range	Code39 (20mil): 40mm~220mm Code39 (5mil): 30mm~60mm QR Code (20mil): 10mm~140mm UPC/ENA 100%: 10mm~160mm
Min Print Contrast / Min. resolution	≥20% Code 39 4 mil
Motion tolerance	3.2M/S
Scan Angle	tilt: 360°, pitch: +60°, skew: +70°
ELECTRONIC	
Interface / Input Voltage	USB, USB-COM, RS232 5VDC+10%
Dimensions / Weight	98(W)×98(D)×142(H) mm 364g (not include cable)
Working Current	130~405 mA
ENVIRONMENTAL	
Temperature (Op/Storage)	Operating: -20°C~+50°C Storage: -20°C~+55°C
Humidity / IP Rating	5%~95% (Non-Condensing) IP54
ESD Protection	±8kV (air discharge), ±4kV (direct discharge)



Dokivision

block B,no.88,ximei Rd,wuxi City,JiangSu Provice.china



Email Support

info@dokivision.com



Direct Contact

+86 021 25460014